

LX / LXP

WHIRLPOOL PEDICURE SPA

User's Manual
Please read user's Manual thoroughly
before using pedicure spa




Table of Contents

Table of Contents

Introduction & Safety

Identify Parts & Description

Consideration

Specification

Dimension

Drainage Connection

Installation Summary

Safety and Maintenance (Dura-Jet)

Safety and Maintenance (Magnetic - Jet)

How to use Magnetic Jet

Discharge Pump

Chair / Backrest attachment

Remote Control Function

Disinfecting Pedicure spa

User Recommendations

UL Certificate

Back Flow Prevention Device (Dual Check valve)













Introduction

Thank you for choosing EPISODE LX series, This finest Whirlpool Pedicure Spa has been develop and Manufactured by J&A USA Inc., to bring quality and exquisitely balanced design yet afford-ability and dependability when properly use. Please read this entire manual thoroughly before installation and use

PLEASE TAKE TIME TO READ THIS MANUAL THOROUGHLY BEFORE USE. If you have any questions or concerning with our pedicure spa, Please contact our customer service and technical support at 631-243-3336 ext 121, Monday through Friday 9AM – 5PM or email us at www.info@jausainc.com

Important requirements

The MFG requires that you contact your local, licensed plumber and licensed electrician to install your new spa. Installation MUST be in compliance with all local and state building codes. Your pedicure spa can not operate efficiently or safely unless it is provided with adequate electrical power, sufficient water pressure, proper water temperature, and required drainage capabilities. Contact your local building inspector for information and local code compliance procedure that need to be followed when having your new pedicure spa installed. Subsequent inspections and approvals that may be required are the responsibility of the purchaser.

Shipment Inspection

Examine the components immediately upon arrival to make sure no damages to the pedicure spa base and chair during the shipment. It is very important that you notify the driver directly and notation should be on the face of the freight bill or bill of lading of any damage. Failure to note damage on the bill of lading may prevent any claims you may have against the carrier.

If concealed or damage is found, you MUST notify the carrier at once and request an inspection. **DO NOT DISCARD THE SHIPPING CARTON** If receiver sign the carrier clean receipt of goods that have been damaged in transit. Do so at your own risk and expense.

Precaution

- Do not stand in the basin of the spa.
- Excessive water temperature is dangerous and should be checked before use. Maximum water Temperature should not exceed 100F (38C).
 - Always enter and exit the spa slowly and carefully.
 - Never bring or operate any electrical device near pedicure spa.
 - The unit has a weight capacity of 250 pounds.


Health Warning


Individuals whose feet or legs are inflamed or have open wounds should not be allowed to use the pedicure spa at any time. The technician should advise clients to consult their physician before using the spa if there is any sign of fungal infection, swelling, fracture, or persistent pain. In some cases diabetics may experience improved circulation in their feet, but should first consult their physician prior to receiving a pedicure.

If the client experiences any pain or discomfort, discontinue the use of the pedicure spa immediately.



Identification






Auto Fill System


(As an optional Only available on Episode LX)


Features & Operation

- a. Automatic spa fill with intelligent and reliable level sensor
- b. Time delay setting
- c. Dual Switched outlets / Control Box
- d. Dual continuous outlets
- e. Single Drain pump controlled outlet with 3 minute timer (If drain pump requested as an Option)
- f. Heavy duty water valve
- g. Operated in automatic or manual mode
- h. Automatically shutdown Jet and LED light If water level in the basin is below the sensor
- I. Built in LED light power supply
- j. Built-in 1 hour timer
- k. Audible overflow warning in manual fill mode

Dura Jet III Built -in
Electrodes Water sensor











Identification





Important Considerations

Electrical Service

110V, 60Hz, 15Amp GFCI protected grounded circuit MUST be used to supply power each individual pedicure spa. And the main circuit breaker MUST be at 25Amp. For maximum of two units per each electrical outlet.

Water Supply

All plumbing connections must conform to local codes.

Water supply to the spa should be provided with adequate water pressure and water temperature.

Water pressure

To fill the basin correctly up to level, Normal water pressure of 30 to 80 P.S.I is required.

Water temperature

The hot water supply temperature must not exceed 140°. Adjust your hot water accordingly. For hot and cold water supply fittings and drain fittings location, see below diagram .Carefully connect the water supply line to the appropriate fittings located on the rear of the pedicure spa.

Pressure / Temperature

Maximum Pressure: 150 psi (10 bars) Minimum Pressure: 10 psi (69kPa)

Working Temperature: 33F to 140F constant; intermittent to 180f

(0.6C to 60C sustained: intermittent to 82.2C)

Recommended Flow: 1.5gpm

UL LISTED / CE CERTIFIED

Compliance with following Code (s): Uniform Plumbing Code, National Plumbing Code of Canada and international Plumbing Code. Also, Compliance with following Standard (s): ASME A112.18.3M / A112.18.1M, CSA B125, NSF / ANSI 61

ANSI - American National Institute, ASME - American Society of Mechanical Engineers, CSA - Canadian Standard Association IAPMO - International Association of Plumbing and Mechanical Officials, UL - Underwriters Laboratory

All J&A USA products has been compliance with requirements for Whirlpool bath appliances contained in ASME / ANSI A122.19.7M-1995, CSA C22.2 No. 68-69

** Vaccum Breaker

Due to Town and / or State requirement/s are varies in building code, if the Town and / or State requires Vaccum Breaker, As the Plumber MUST provide Vaccum Breaker according to building code requirement.

Drain Facilities

The pedicure spa Drain must meet local plumbing codes. Check valve for Drain (not Provided) Must be installed by a licensed plumber. Also Pedicure spa must be securely fasten to the floor.


Installation Summary


The installation must comply with local, state, and federal building, plumbing and electrical codes, where applicable. A licensed plumber should complete the plumbing of the pedicure spa.

Note: Failure to comply with federal, state, or local codes and ordinances will result in warranty being nullified and void.



Specification





Specification

Plumbing Source

Dimension & Weight (Shipping) Pedicure Spa & Massage Chair 6/L x 3/W x 40H	242 105	242 lbs	
Stool 20.25L x 8.5H x 2	0W 19 lbs		

Dimension & Weight (Net) Pedicure Spa & Massage Chair 57 3/4"L x 28"W x 56"H 182 lbs.

Capacity of Tub Episode LX 4.5 U.S Gallon

Switch On / Off Air Activated Switch

Power Source Dedicated 15Amp Wall Outlet Require

Pipe - less whirlpool motor 120Vac, 0.4 Amp. 60Hz, Discharge Pump (Optional) 120Vac, 60Hz


Massage System 120Vac, 60Hz


Hot Water 0.5 inches (Fitting Provided)
Cold Water 0.5 inches (Fitting Provided)


Drain 1.5 inches (See Plumbing Instruction)

Warranty Unit One Year Optional Item 120 Days










Installation Specifications Summary

Warning: Failure to comply with federal, state or local codes and ordinances will result in warranty being null and void.

As stated, the pedicure spa installation must comply with all **plumbing and electrical codes**. A licensed plumber and licensed electrician MUST complete the applicable connections of the pedicure spa.

Location and support


Select a level location. The floor structure beneath the pedicure spa must be capable of supporting the occupied pedicure spa.





Due to continuous improvements on all our products, specification, characteristics, packing, color, designs are subject to change without notice.




DRAIN










Dura-Jet III

Safety Instructions

When using electrical equipment, basic safety precautions should always be followed to reduce the risk of fire, electrical shock, and injury to persons, including the following:

- 1. Read and follow all instructions before using the equipment.
- 2. Keep the cord out of heavy traffic area. To avoid fire hazard NEVER put the cord under the rugs, near heat generating devices.
- 3. Always turn off the equipment before servicing.
- 4. Do not drop or insert any object into any openings.
- 5. Do not operate any equipment with a damage parts.
- 6. Any other use not recommended by the manufacturer may electrical shock or injury to persons.
- 7. Never use outdoors
- 8. Do not attempt to repair or adjust any electrical or mechanical functions on the unit.



- 1. Dual powerful massage jet-streams
- 2. Jet assembly can be attached from the pump for quick cleaning and sanitizing.
- 3. Built-in electronic sensor for pump control.
- 4. AC motor (long life)
- 5. Extremely low power consumption.
- 6. Manufactured in USA.

Cleaning Instruction

- 1. Ensure the unit is off
- 2. Remove the front cover
- 3. Remove the impeller and impeller cover
- 4. Use anti-bacterial solution (EPA registered) to clean all plastic parts.
- 5. Reassemble the front cover

DURA-JET III Specifications

Model: DURA_JETIII -120Vac, 0.4 Amp. 60Hz,

Pump: Dual Air Jet Flow

Mounting: Single 3.5" hole


Auto tighten Mounting screws(4)

MAGNA-JET (OPTIONAL)

Safety Instructions

When using electrical equipment, Basic safety precautions must be followed to reduce the risk of fire, electrical shock, and injury to Persons.

- 1. Read and follow all instructions before using the equipment.
- 2. Keep electrical cord out of heavy traffic area. To avoid fire hazard NEVER place electrical cord under the rug, near heat Generating devices.
- 3. Always turn power off the equipment before service.
- 4. Do not drop or insert any object into any openings.
- 5. Do not operate any equipment with damaged parts.
- 6. Any other use not recommended by the manufacturer may cause electrical shock or cause injury to person/s.
- 7. Never use it outdoors
- 8. Do not attempt to repair or adjust any electrical or mechanical.



Cleaning Instruction

- $1. \ Turn\ off\ the\ unit\ and\ wait\ until\ the\ motor\ is\ fully\ stops.$
- 2. Hold Hydro whirlpool jet cover firmly and pull to separate from the round magnetic field.
- 3. Turn hydro whirlpool jet cover to left to open and pull out impeller.
- 4. Use Anti Bacterial solution (EPA Registered) to clean all parts.
- 5. After sanitize all parts, place impeller and close hydro whirlpool jet cover to turn right to lock
- 6. Hold firmly the whirlpool cover jet and gently place it onto the round magnetic field. Do not release the hydro whirlpool jet cover until Jet cover is on the round magnetic housing.

MAGNA-JET Specifications

Model: MAGNA-JET - 120VAC, 60Hz, 1.0Amp,

Pump: Hydro-Massage Dual jet Flow

Mounting: Single 3.5" hole Diameter

Auto tighten Mounting screws(4)

WARNING: DO NOT RUN DRY, BASIN MUST FILLED WITH WATER TO LEVEL INDICATOR.


CAUTION: MAGNETIC JET COVER ASSEMBLY MUST ALIGN WITH DISCHARGE PORT POSITIONED AT 3/9 O'CLOCK.




WHEN READY TO USE, **MAKE** SURE JET COVER IS POSITIONED AT **3 /9 OCLOCK** FOR PROPER WHIRLPOOL ACTION IN THE BASIN. IF JET COVER IS **NOT** ALIGN AT 3/9 O'CLOCK, WATER WILL SPLASH OUTSIDE OF THE BASIN.

PROPER WAY TO USE MAGNETIC JET SYSTEM

- 1- FILL THE WATER TO WATER LEVEL INDICATOR.
- 2- HOLD MAGNETIC JET FIRMLY TO BRING CLOSER TO THE ROUND MAGNETIC FILED AND DO NOT RELEASE THE MAGNETIC JET PREMATURELY OR THIS WILL CAUSE IMPACTS ON THE JET COVER AND THE ROUND MAGNETIC FIELD(HOUSING) SHORTENING THE LIFE EXPECTANCY OF THE JET COVER. WHEN THE JET COVER NEARS THE ROUND MAGNETIC FIELD, PLACE JET COVER ONTO THE FOUR DIMMPLE AREA (SEE DIAGRAM). THE JET COVER MUST ALIGN WITH DISCHARGE PORTS POSITIONED AT 3/9 O'CLOCK.
- 3- WHEN FINISHED WITH CLIENT, DO NOT REMOVE MAGNETIC JET UNTIL MOTOR IS FULLY STOPPED.
- 4- WHEN MOTOR IS FULLY STOPPED, REMOVE MAGNETIC JET COVER FROM THE MOTOR AND REMOVE JET COVER AND IMPELLER FOR SANITIZATION.





inside of base)

Installation Instruction


- 1. Make a hole (size 1-3/8") for the On/Off switch as shown (see fig 1). Predrill required.
- 2. Placed a 1/8" clear hose into the rear of the switch and on/off switch into the hole.
- 3. The discharge pump kit is made to fit onto the pedicure unit. (see fig 2)
- 4. Connect E-Z connector onto the drain elbow.
- 5. Plug discharge pump outlet into the two minute timer outlet
- 6. Plug two minute timer into the wall outlet.
- 7. It is very important that tip of the clear tub remain above the water Level with one loop as shown.

** Please cut to fit 1" Flex hose to your size**

Operation Instruction

Warning! DO NOT RUN DRY

- 1. Turn to open drain plug. 3 to 5 second for air to release from the pipe
- 2. Press On/Off switch to activate timer.
- 3. At any time, water drain completely from the basin. Press On/Off switch to stop or built in two minute timer.



3/8" Clear Tube from on/off for D/P pump insert into 2 Min. Timer.
Make sure to push in tightly.






Figure 1


Recliner Piston End Attachment Instruction



CORRECT PIN POSITION



WRONG PIN POSITION



A. PLEASE MAKE SURE PIN LOCATED AT THE END OF RECLINER PISTON IS IN HORIZONTAL POSITION. B. SLOWLY BRING UP THE BACKREST TO UP RIGHT POSITION UNTIL YOU HEAR "CLICKING" SOUND TO ENSURE PROPER PIN ENGAGEMENT INTO LOCKING LATCH.



Remote Control Functions



INCLINE

Press down to move chair To desirable angle.



FORWARD

Press to hold to move chair to desirable position



AUTO

Pre-Programed Automatic Massage with 2 Selection



POSITION

User's Height (HIGH / MID / LOW)



WHEEL

Adjust Massage Wheels Up and Down to desirable position.

KNEADING


3 Selections of Kneading Intensity

KNOCKING

Impulse Tapping Massage.
2 Selections of Knocking Intensity

VIB

2 Selections of Intensity for Seat vibration Massage.



POWER

On / Off



BACKWARD

Press to hold to move chair to desirable position



RECLINE

Press down to move chair To desirable angle.



MANUAL

Press for Manual MODE with Time Selection of 10~30 Mins.



RANGE

FULL / PARTIAL / SPOT 3 Selections



MSG

Keep Pressing to Massage Wheel to the intended Massage Width.

COMB

Kneading / Tapping / Knocking Combinations

TAP

3 Slections of Tapping intensity

SHIATSU

- 1. Press Manual / Timer to choose Shiatsu Massage Time Selection
- 2. Press Massage Range to Select FULL or PARTIAL Travel Position.
- 3. Press Tapping Width to fine tunecomfort.

DISINFECTING YOUR PEDICURE SPA

<u>Note:</u> Please be advised that it is responsibility of purchaser/user to adhere strictly to the following procedure. Any non-compliance will be considered negligence of the purchaser/user.

The Bureau of barbering and cosmetology requires that salons using whirlpool pedicure spas use the following disinfecting Procedures to ensure proper cleaning and maintenance of the equipment, and to prevent bacterial infection. For your clients safety, always use the regulations as a minimum standard for cleaning and disinfecting.

Chair maintenance

Please see chair manual for Do and Don't

At the end of the day:

- 1. Remove the intake suction screen, All debris trapped behind the screen of each pedicure spa must be removed. And the screen and the inlet shall be washed with soap or detergent and water
- 2. Before replacing the screen, Totally immersed the screen into an EPA- registered disinfectant with bactericidal, Fungicidal, and virucidal activity.
- 3. Finally, flush the whirlpool system with low-suding detergent and warm OR an EPA registered cleanser for 10 minutes. Rinse with clean fresh water and drain.

Note:

Cleaning or sanitizing is NOT disinfecting. According to the CDC and EPA, disinfecting occours only when there is a reduction of pathogenic microbes at 99.999%. Sanitizing is a only reduction of 99.9%. Cleaning of whirlpool pedicure spa requires surfactant and chelating detergents that are low foaming and have ability to remove body oils, organic oil additives, mineral oil, skin cell, nail clippings, etc.. that can accumulate both in the basin and the jets which may become fertile area for micro organism to grow.

Note:

The use of oil based products can build up in the whirlpool system causing clogging in the jet and build up onto the surface of the basin. Adherence to the above cleaning will minimize build up thus the manufacturer recommend not to use mineral oil based product.

USER RECOMMENDATION

PLEASE READ THE MANUAL THROUGHLY BEFORE USE TO ENSURE CORRECT OPERATION.

THOSE UNDER A DOCTORS CARE OR WHO ARE EXPERIENCING ONE OR MORE OF THE FOLLOWING DONDITIONS SHOULD CONSULT THEIR DOCTOR BEFORE USE.

- You are receiving medical treatment or are feeling ill.
- Your body shows any cute symptoms.
- You have heart disease.
- You are pregnant or having a menstrual period.
- Your doctor has ordered you to rest.
- You have a back disorder resulting from an accident or disease.
- You have a high fever.
- You have sensory disorders.
- You have medical electrical device (e.g. pacemaker).
- You have service interruption in the circulation of the legs.
- You are diabetic.

FAILURE TO DO SO MAY RESULT IN ACCIDENTS AND HEALTH PROBLEMS.







CERTIFICATE OF COMPLIANCE

Certificate Number 20140428-E242637

Report Reference E242637-20040930

Issue Date 2014-APRIL-28

Issued to: J & A USA INC

335 CROOKED HILL RD BRENTWOOD NY 11717

This is to certify that representative samples of

PLUMBING ACCESSORIES

USL, CNL - Commercial-type, Whirlpool Pedicure Spas, Models Cleo, Episode S-type, Lenox, Pacific and Petra Model designation may be followed by any two-letter suffix, not related to safety such as finish, special features etc

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: Standard for Electric Plumbing Accessories, UL 1951

Standard for Motor Operated Appliances (Household and

Commercial), CSA C22.2 No. 68-09

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers: "US" the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

William R. Carney

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



Back Flow Protection Device (Dual Check Valve)

May.1.2014

In accordance with applicable Local or State regulations,

J&A USA Inc., The manufacturer of the pedicure whirlpool spa certifies that the following models are equipped with factory installed Dual Check Valve back flow preventer:

- ** Lenox Series
- ** Cleo Series
- ** Episode Series
- ** Pacific Series
- ** Petra Series
- ** Toepia Series

The specification of the installed device is as follows:

DEVICE NAME	DUAL CHECK VALVE BACKFLOW PROTECTION				
DEVICE MANUFACTURER	NEOPERL INC. Waterbury CT.				
DEVICE MODEL	Dual Check Valve 1/2" x /2"NPT				
DEVICE SPECIFICATION	TESTED AND CERTIFIED TO MEET NSF/ASSI 61 Complies with ANSI/ASME A112.18.3M, A112.18.1M AND CSA B125				
DEVICE PRESSURE	MAXIMUM PRESSURE: 150 PSI (10 BAR) SERVICE PRESSURE: 80 PSI				
DEVICE TEMPERATURE	MAXIMUM TEMPERATURE : 150F SERVICE TEMPERATURE : 90F				

ALL MODELS OF PEDICURE SPA MENTIONED ABOVE ARE EQUIPPED WITH THE SUBJECT DEVICE AS STANDARD FEATURE. As for your information, indicated State requires Vaccum Breaker.

** Effective April 01 2005:

ARIZONA, CALIFORNIA, NEBRASKA, NEVADA, OREGON, TEXAS AND WASHINGTON

** Effective June 15 2005:

ILLINOIS, MINNESOTA, WISCONSIN, MICHIGAN

** Effective May 01 2007: CONNECTICUT

For additional information, Please contact us at 631-243-5300 Very Truly yours,

Technical Support

Limited Warranty

Pedicure Spa

IMPORTANT

To validate the limited warranty, The Limited Warranty Registration Form MUST be filled out completely and return to J&A USA within 30 days of original purchased date. This Limited Warranty is valid if J&A USA received registration form.

J&A USA Inc. Pedicure Spas has designed and manufactured with the highest standards and expressly warrant the pedicure spa as follows:

To the original owner of the J&A USA Inc. Pedicure Spa may repair or replace, at its option, any pedicure spa found to be defective in material or workmanship upon inspection by a authorized representative of J&A USA Inc. This limited warranty covers the following:

Base - Twenty four (24) month from date of shipment from J&A USA facility.

Components / Parts - Twenty four (24) month from date of shipment from J&A USA facility.

Stool - Ninety (90) days from date of shipment from J&A USA facility.

Shipping Costs - Twenty four (24) month from date of shipment. J&A USA will cover normal shipping costs associated with replacement parts. Expedited shipping cost will incur an additional charge.

Labor - Twelve (12) month from date of shipping, J&A USA Inc will cover reasonable labor costs associated with the installation of replacement parts found to be defective in material or workmanship upon inspection by authorized representative of J&A USA INC.

No labor cost or replacement parts will be covered under this limited warranty if at the sole discretion of J&A USA INC. it is determined a failure was caused by negligence, accident or improper use, improper installation or lack of proper maintenance as in the Owner's Manual.

NO CONSEQUENTIAL, INCIDENTAL, CONTINGENT, INDIRECT, SPECIAL OR OTHER DAMAGES WILL BE

ALLOWED. This warranty is null and void if the pedicure spa is removed from its original installation or is not installed accordance with specifications of pedicure spa or national, state or local codes, regulation and ordinances. Furthermore, this limited warranty is null and void if the pedicure spa is subjected to improper installation or maintenance, negligence, improper cleaning or any other circumstance beyond J&A's control. To validate limited warranty, pedicure spa must be installed by a licensed plumber and/or electrician in accordance with local and / or State code and pedicure spa installation instructions.

Warranty Exclusion

- 1- Unauthorized repairs and/or modification or tampered in any way.
- 2- Damage due to freight, accident, natural disaster and /or abuse or misuse
- 3- Stain, fading or discoloration of seat, back cover, armrests (Upholsteries), Tray or Footrest
- 4- Fading, discoloration or staining of basin or Any portion of surface of pedicure spa caused by water additive or improper water treatment (such calcium built up) and/or cleaning agents/s
- 5- Damage or malfunction due to improper installation including but not limited to, failure to comply with all national, state and local plumbing, electrical and building codes.
- 6- Magnetic jet assembly (base, impeller and cover) due to J&A provided an extra jet assembly to accommodates wear-tear.
- 7- Damage drain pump due to residue built up in drain pipe and / or due to the lack of maintenance.

Parts for which labor / Service is NOT COVERED - Following components are simple to replace and DO NOT require a service technician. Therefore, though the part is covered under the guidelines of the warranty agreement.

- 1- Panel
- 2- Jet cover, impeller and / or jet assembly
- 3- Faucet Cartridge, Shower Head
- 4- Footrest
- 5- Air actuate On/Off Button
- 6- Drain Plug
- 7- Remote control

During the Limited Warranty period, J&A will, at its sole discretion, repair or replace any defective component. All component parts removed under this Limited Warranty become property of J&A USA Inc. And all replacement component /s MUST be return to J&A USA Inc. within 20 days of replacement. If not, replaced component/s will be charge as its cost/s.

This limited warranty is for the original owner and **not** transferable. The original owner agrees by using pedicure spa the obligation of J&A USA shall not extend to indirect or contingent damage or injury. Furthermore, the obligations of J&A are limited to those set forth herein. The limited warranty is the exclusive remedy and is in lieu of all other warranties, express or limited, including but not limited to, any implied warranty of fitness or merchantability for a particular purpose. No distributor or other person has the right or authority to bind J&A USA INC to changes to this limited warranty. Consequently, J&A USA INC is **not** responsible for such warranties or representations.

Limitation of liability

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT FOR THE OBLIGATIONS SPECIFICALLY SET FORTH IN THIS WARRANTY STATEMENT, IN NO EVENT WILL J&A OR ITS THIRD PARTY SUPPLIERS BE LIABLE FOR ANY DAMAGED CAUSED BY J&A'S PEDICURE SPA OR THE FAILURE OF J&A PEDICURE SPA INCLUDING ANY LOST PROFIT OR SAVINGS, BUSINESS INTERRUPTION, LOSS OF USE OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS OF ANY KIND, OR SPECIAL, INCREMENTAL, OR CONSEQUENTIAL DAMAGES. THIS LIMITATION OF LIABILITY APPLIES WHETHER DAMAGES ARE SOUGHT, OR A CLAIM MADE, UNDER THIS LIMITED WARRANTY OR AS A TORT CLAIM, A CONTRACT CLAIM OR ANY OTHER CLAIM.

Limited Warranty Registration Form

IMPORTANT

To validate the limited warranty, The Limited Warranty Registration Form MUST be filled out completely and return to J&A USA within 30 days of original purchased date. This Limited Warranty is valid if J&A USA received registration form.

			-		
Serial No.:				Area Code:	Phone:
J A			Tel (Salor		
	E-Mail Address:		Tel (Salol	Area Code:	Phone:
Tour Salon I	L-Iviaii Audi ess.		Ca		Thore:
			Ce	:11	
First Name	:	Last Name:		Date	of Purchase (mm/dd/yyyy):
C I N					
Salon Name	:				
Salon Addr	ess:				
City:					
State:	Zip Code:				
Name of Dis	tributor :				
City:			St	tate:	Zip Code:
Completed V	Varranty Registration	Form to: J&	A USA Inc.		
r		335 Crooked Hill R	oad Brentwood		
		or Fax to 631-243-3339	or email to info	o@jausainc.co	m
Questionnair	e (We value your voice	e!)			
1. Ar	e you satisfy with Pe	edicure spa received?	Yes:	No:	
		•			
2. Ar	e you currently using	J&A product/s? If so, How le	ong? Yes:	No:	Year/s
2. If 1	not, What other produ	ict?			
	_				
4. WI	nat is the most import	ant features in choosing Pedi		rand Desig	
. TT			Pi	rice Utner	
5. Ho	ow long in business?		Y	Year/s	
6. Ho	ow often are you remo	odel Your Salon?		Year/s	
	•				
7. W	ould you purchase J&	A product in the future?	Yes:	No:	
				_	
8. Do	you want to receive	a promotion by email?	Yes:	No:	
9. Ar	y suggestion or Com	ment			